

जा.क्र.शावैमहाआ/बांधकाम / ६६९ /२६

दि. १३.०२.२०२६

मुलींच्या वसतिगृहामध्ये मेस करिता शेड तयार करणे करिता जाहिर ई-दरपत्रक सूचना

शासकीय वैद्यकीय महाविद्यालय, अमरावती च्या मुलींच्या वसतिगृहामध्ये मेस करिता शेड तयार करणे करिता इच्छुक पुरवठादारांकडून द्विलिफाफा प्रधतीन दरपत्रक मागविण्यात येत आहे. सदर कालावधी दरनिश्चिती पत्र निघाल्याच्या दिवसापासून १८० दिवसांकरिता राहील.

- १) **तांत्रिक लिफाफा** –या लिफाफ्यामध्ये पुरवठादाराने बांधकामा बाबतचा परवाना, भुतकाळातील कामाचा अनुभव प्रमाणपत्र, साईड इंजिनियर नियुक्ती बाबतचे प्रमाणपत्र, कामगाराची नोंदणी विमा आणि सुरक्षातेबाबतचे कागदपत्र जीएसटी प्रमाणपत्र व पॅन कार्ड, आधारकार्ड या कागदपत्राच्या छ्यांकित प्रती टाकून तो मोहोरबंद करण्यात यावा त्यावर स्पष्ट शब्दात तांत्रिक बाबींचा लिफाफा असे नमुद करून स्वतःचे नाव व पत्ता व लिहावा त तो मोहोरबंद करावा.
- २) **किमंतीचा लिफाफा** – ज्यामध्ये दर नमुद असलेला कागद स्वाक्षरी व सहीनिशी टाकण्यात यावा व त्यावर स्पष्ट अक्षरात किमंतीचा लिफाफा नमुद करून स्वतःचे नाव व पत्ता लिहावा व तो देखील मोहोर बंद करण्यात यावा.

उपरोक्त दोन्ही लिफाफे एका मोठ्या लिफाफ्यामध्ये टाकून दरपत्रक अधिष्ठाता, शासकीय वैद्यकीय महाविद्यालय, अमरावती यांचे नावे सादर करावयाचे असुन दरपत्रकाच्या लिफाफ्यावर शासकीय वैद्यकीय महाविद्यालयाकरिता आवश्यक असलेल्या मुलींच्या वसतिगृहामध्ये मेस करिता शेड तयार करणेकरिता दरपत्रक असे स्पष्ट नमुद करण्यात यावे. स्वतःचे नाव व पत्ता लिहावा अशा प्रकारे तयार करण्यत आलेले दरपत्रक दि. २५/०२/२०२६ रोजी सायंकाळी ०६:०० वाजेपर्यंत कार्यालयात आणून देण्यात यावे. तांत्रिक लिफाफा मध्ये दराचा उल्लेख करू नये. त्यामध्ये दर आढळल्यास दरपत्रक अग्राह समजन्यात येईल.

प्राप्त होणाऱ्या दरपत्रकातील तांत्रिक लिफाफे दि. २६/०२/२०२६ रोजी दु. १२:०० वाजता अधिष्ठाता, शासकीय वैद्यकीय महाविद्यालय, अमरावती यांच्या दालणामध्ये उघडण्यात येईल. सर्व प्रथम तांत्रिक बाबींचे लिफाफे उघडण्यात येईल. तांत्रिक बाबींची पुरता झाली नसल्यास संबंधीत पुरवठादाराचे दरपत्रक रद्द समजण्यात येईल व त्याचे किमंतीचे लिफाफे उघडण्यात येणार नाही. इच्छुक पुरवठादारास सदर सभेस उपस्थित राहता येईल.

जिथे दर द्यावयाचे नाही तिथे इच्छुक नाही असे स्पष्ट नमुद करावे. ती जागा रिकामी सोडण्यात येवू नये. सर्व दर हे एका नगाकरिता सर्व कर समाविष्ट करून नमुद करावे. अपुर्ण माहितीसह प्राप्त होणारी दरपत्रक नाकारण्याचा अधिकारी अधिष्ठाता यांनी राखून ठेवलेला आहे. तसेच यादी मधील काही बाबी किंवा मागविण्यात येणाऱ्या संपुर्ण दरपत्रकाची प्रक्रिया रद्द करण्याचा अधिकारी अधिष्ठाता यांनी राखून ठेवलेला आहे.

दर हे पेनने लिहीन्यात येऊ नये ते प्रिंट केलेले असावे. हसताक्षरात लिहिलेले दरपत्रक रद्द करण्यात येईल. दरनिश्चिती झालयावर आवश्यकतेनुसार वेळोवेळी आदेश काढण्यात येईल. आदेश प्राप्त होताच १० दिवसांत आदेशातील मालाचा पुरवठा करणे बंधनकारक राहील.

न्युनतम ठरणाऱ्या पुरवठादारास नमुद विनिदिष्टांप्रमाणे सदर साहित्याचे पुरवठा करणे बंधनकारक राहील. अन्यथा पुरवठा करण्यात आलेले साहित्य तातडीने बदलून देण्याचे करावे. तसेच सदर साहित्याचा पुरवठा करणे बंधनकारक राहील. त्याकरिता कोणत्याही प्रकारचा अगाऊचा खर्च या संस्थेमार्फत अदा करण्यात येणार नाही.

सदर दरपत्रकासंबंधी आपणास काही तक्रार या कार्यालयास दाखल करावयाची असल्यास प्रथम आपण या कार्यालयात तक्रार संबंधी रु. १०,०००/- शासन खाती जमा करावे लागेल. जर आपण दाखल केलैल्या तक्रारीत या कार्यालयास काही तथ्य आढळून आल्यास आपणास आपण शासन खाती जमा केलेली रु. १०,०००/- रक्कम परत करण्यात येईल. तक्रारीमध्ये काही तथ्य न आढळल्यास रु. १०,०००/- रक्कम परत करता येणार नाही व ती रक्कम शासन खाती जमा करण्यात येईल.

13-02-2026
(डॉ.एन.जी.राऊत)
अधिष्ठाता
शासकीय वैद्यकीय महाविद्यालय, अमरावती

Government Medical College, Amravati

E Quotation for Construction of Shed for Girls Hostel Mess at at GMC, Amravati
Tq. Dist. Amravati

Item No.	Item of Work	Rate
1	Excavation for foundation in earth, soil of all types, sand, gravel and soft murum, including removing the excavated material up to a distance of 50 m. beyond the building area and stacking and spreading as directed, dewatering, preparing the bed for the foundation and necessary back filling, ramming, watering Mechanical Means including shoring and strutting etc. complete. (Lift upto 1.5 m.) By Mechanical Means .	
2	Excavation for foundation in hard murum including removing the excavated material upto distance of 50 metres beyond the building area and stacking and spreading as directed, dewatering, preparing the bed for the foundation and necessary back filling, ramming, watering including shoring and strutting etc. complete. (Lift upto 1.50 m) By	
3	Providing soling using 80mm size trap metal in 15 cm. layer including filling voids with Crushed sand/grit, ramming, watering etc. complete.	
4	Providing and laying Cast in situ/Ready Mix cement concrete in M-10 of trap/ granite/ quartzite/ gneiss metal for foundation and bedding including bailing out water, Steel centering, formwork, laying/pumping, compacting, roughening them if special finish is to be provided, finishing if required and curing complete, with fully automatic micro processor based PLC with SCADA enabled reversible Drum Type mixer/concrete Batch mix plant (Pan mixer) etc. complete. With fine aggregate (Crushed sand VSI Grade	
5	Providing and laying in situ /Ready Mix cement concrete M-20 of trap/granite/quartzite/ gneiss metal for R.C.C. work in foundations like raft, strip foundations, grillage and footings of R.C.C. columns and steel stanchions etc. including bailing	
6	Providing and fabricating structural steel work in rolled sections like joists, channels, angles, tees etc. as per detailed design and drawings or as directed including cutting, fabricating, hoisting, erecting, fixing in position making riveted / bolted /welded connections without connecting plates, braces etc. and including one coat of anticorrosive paint and over it two coats of oil painting of approved quality and shade etc. complete	
7	Providing and fixing colour coated Zincalume (R) AZ150 (min 150 gms/sq.mt. total on each side) profiled sheets for roofing. The feed material is manufactured out of nominal 0.45 mm Base Metal Thickness (BMT) (0.5 mm TCT), Hi-strength steel with min.550 MPa yield strength, metallic hot dip coated with Aluminium-Zinc alloy (55% aluminium 43.4% zinc 1.6% silicon) with COLORBOND (R) steel quality super durable polyester paint coat (with inorganic pigment). The paint shall have a total coating thickness of nominal 35	

	um, comprising of nominal 25 um exterior coat on top surface and nominal 10 um reverse coat on back surface. Profile sheet shall have nom. 950- 1050 mm effective cover width and nominal 25-30 mm deep ribs	
8	Providing and fixing plain zinc sheeting of 0.80 mm thick (22 B.W.G.) over the ridge hip or valley to galvanized iron sheet roofing including all fastening and bolt galvanised iron screws and bolts, lead and bitumen washers etc. complete.(Weight of 6.8	
9	Providing and fixing M.S. grill door 24 Kg/Sqm of various size as per detailed drawings without hot dip coating, iron fixtures and fastenings and 3 coats of oil painting etc	
10	Providing and fixing mild steel grill work for windows, ventilators etc. 20 Kg/Sqm as per drawing including fixtures, necessary welding and painting with one coats of anticorrosive paint and two coats of oil painting complete.	
11	Providing and laying vitrified mirror / glossy finish tiles decorative type having size 590 mm to 605 mm x 590 mm to 605 mm of 8 to 10 mm thickness and confirming to IS. 15622-2006 (group Bla) of approved make, shade and pattern for flooring in required position laid on a bed of 1:4 cement mortar including neat cement float, filling joints, curing and clearing etc. complete.	
12	Providing and fixing coloured glazed earthenware Wash Hand Basin of 55cm x 40 cm size including cold water pillar tap/cold and hot water pillar tap brackets, rubber plugs and brass chain, stop tap and necessary pipe connection including P.V.C. waste pipe and trap up to the outside face of the wall. Making good the damaged surface, testing etc. complete.	
13	Royalty charges Sand	
14	Royalty Charges Murum/80mm	
15	Basic test of cement	
16	Basic test of Aggregate Water Absorption, Sp Gravity, Impact/ crushing value	
17	test of Sieve analysis of aggregate	
18	test of Fineness modulus of sand	
19	test of Steel, Ultimate tensile strength, %elongation, Wt/meter	
20	test of Compression test of CC cube	
21	test of Bricks, Water absorption, Comp. strength, efflorescence	
Total		

The Detail MEASUREMENT of the said work is attached Herewith Below.

Chait 13.02.2026
(Dr.N.G.Raut)

Dean
Government Medical College, Amravati

Dean
Govt. Medical College
Amravati

NAME OF WORK :

Construction of Shed for Girls Hostel Mess aT GMC Amravati. Tq. Dist. Amravati.

MEASUREMENT

Item No.	Item of Work	No	L	B	H	Quantity	Unit
----------	--------------	----	---	---	---	----------	------

1 Excavation for foundation in earth, soil of all types, sand, gravel and soft murum, including removing the excavated material up to a distance of 50 m. beyond the building area and stacking and spreading as directed, dewatering, preparing the bed for the foundation and necessary back filling, ramming, watering including shoring and strutting etc. complete. (Lift upto 1.5 m.)

By Mechanical Means

for columns	10	x 0.91	x 0.91 =	1.22	10.10
for tile flooring	1	x 19.00	x 5.00 =	0.30	28.50
	0	x 0.00	x 0.00 =	0.00	0.00

38.602 Cum

2 Excavation for foundation in hard murum including removing the excavated material upto distance of 50 metres beyond the building area and stacking and spreading as directed, dewatering, preparing the bed for the foundation and necessary back filling, ramming, watering including shoring and strutting etc. complete. (Lift upto 1.50 m) By Mechanical Means

for columns	0	x 0.00	x 0.00 =	0.00
for steps	0	x 0.00	x 0.00 =	0.00

0.000 Cum

3 Providing soling using 80 mm size trap metal in 15 cm. layer including filling voids with Crushed sand/grit, ramming, watering etc. complete.

for columns	10	0.91	0.91	x 0.15 =	1.24
for tiles flooring	1	x 18.30	x 4.87 =	x 0.15 =	13.37
	0	x 0.00	x 0.00 =	x 0.00 =	0.00

14.610 Cum

Item No.	Item of Work	No	L	B	H	Quantity	Unit
4	Providing and laying Cast in situ/Ready Mix cement concrete in M-10 of trap/ granite/ quartzite/ gneiss metal for foundation and bedding including bailing out water, Steel centering, formwork, laying/pumping, compacting, roughening them if special finish is to be provided, finishing if required and curing complete, with fully automatic micro processor based PLC with SCADA enabled reversible Drum Type mixer/concrete Batch mix plant (Pan mixer) etc. complete. With fine aggregate (Crushed sand VSI Grade)						
	for columns	10	x 0.91	x 0.91	x 0.10 =	0.83	
	for tiles floor	1	18.3	x 4.87 =	x 0.10 =	8.91	
		0	x 0.00	x 0.00 =	x 0.00 =	0.00	
						9.740	Cum
5	Providing and laying in situ /Ready Mix cement concrete M-20 of trap / granite /quartzite/ gneiss metal for R.C.C. work in foundations like raft, strip foundations, grillage and footings of R.C.C. columns and steel stanchions etc. including bailing out water, Steel centering formwork,						
	for pedestals	10	x 0.61	x 0.61	x 0.91 =	3.386	
						3.386	Cum
16	Providing and fabricating structural steel work in rolled sections like joists, channels, angles, tees etc. as per detailed design and drawings or as directed including cutting, fabricating, hoisting, erecting, fixing in position making riveted / bolted /welded connections without connecting plates, braces etc. and including one coat of anticorrosive paint and over it two coats of oil painting of approved quality and shade						
	square section of 49.5x2.9 mm vertical post	10	x 3.05	x 4.07 =	kg/mtr	0.124	
	square pipe vertical comp.member 38x2.6	5	x 1.50	x 2.75 =	kg/mtr	0.02	
	for rafters 38x2.6 mm (one side slant rafters)	5	x 5.10	x 2.75 =	kg/mtr	0.07	
	Square section of 38x2 mm purlins	6	x 18.30	x 2.75 =	kg/mtr	0.301	
	square pipes for bracing 38x2	2	x 4.10	x 2.75 =	kg/mtr	0.022	
	Tie beam 38x2	7	x 4.87	x 2.75 =	kg/mtr	0.093	
	For Plates 0.6*0.6*8 mm	x 30	x 0.36	x 62.80	kg/sqm	0.678	
						1.308	MT

Item No.	Item of Work	No	L	B	H	Quantity	Unit
----------	--------------	----	---	---	---	----------	------

17 Providing and fixing colour coated Zincalume (R) AZ150 (min 150 gms/sq.mt. total on each side) profiled sheets for roofing. The feed material is manufactured out of nominal 0.45 mm Base Metal Thickness (BMT) (0.5 mm TCT), Hi-strength steel with min.550 MPa yield strength, metallic hot dip coated with Aluminium-Zinc alloy (55% aluminium 43.4% zinc 1.6% silicon) with COLORBOND (R) steel quality super durable polyester paint coat (with inorganic pigment). The paint shall have a total coating thickness of nominal 35 um, comprising of nominal 25 um exterior coat on top surface and nominal 10 um reverse coat on back surface. Profile sheet shall have nom. 950-1050 mm effective cover width and nominal 25-30 mm deep ribs with subtle square fluting in the five pan at nominal 180-250 mm center- to-center. The end rib shall be designed for anti-capillary groove. and return leg. The feed material should have coil manufacturers product details marked a regular interval. Including fasteners with min. fastened with min. 25 um Zinc-Tin alloy coated, Hex head, self-drilling screw

roof	1	x 18.30	x 5.10	93.330
	1	x 18.30	x 1.50	27.450
	1	x 2.44	x 1.50	3.652
	1	x 18.30	1.2	21.960
	2	x 4.87	x 3.05	29.707
	1	x 3.05	x 3.05	9.302
	1	x 18.30	x 2.74	50.142
deduction of door	2	x 1.20	x 1.20	2.880
				232.663 Sqm

18 Providing and fixing plain zinc sheeting of 0.80 mm thick (22 B.W.G.) over the ridge hip or valley to galvanized iron sheet roofing for trusses closing

1	x 18.30	x 0.60	10.980
0	0	x 0.00	0.000
			10.98 Sqm

19	Providing and fixing M.S. grill door 24 Kilogram/ One Square Metre of various size as per detailed drawings without hot dip coating, iron fixtures and fastenings and 3 coats of oil painting etc.	2	x 1.20	x 2.10 =	2.52	Sqm
20	Providing and fixing mild steel grill work for windows, ventilators etc. 20 Kilogram/ One Square Metre as per drawing including fixtures, necessary welding and painting with one coats of anticorrosive paint and two coats of oil painting complete.	1	x 18.30	x 3.05 =	55.815	Sqm

Item No.	Item of Work	No	L	B	H	Quantity	Unit
21	<p>Providing and laying vitrified mirror / glossy finish tiles decorative type having size 590 mm to 605 mm x 590 mm to 605 mm of 8 to 10 mm thickness and confirming to IS. 15622-2006 (group Bla) of approved make, shade and pattern for flooring in required position laid on a bed of 1:4 cement mortar including neat cement float, filling joints, curing and clearing etc. complete.</p>	1	x 18.30	x 4.87		89.121	Sqm
22	<p>Providing and fixing coloured glazed earthenware Wash Hand Basin of 55cm x 40 cm size including cold water pillar tap/cold and hot water pillar tap brackets, rubber plugs and brass chain, stop tap and necessary pipe connection including P.V.C. waste pipe and trap up to the outside face of the wall. Making good the damaged surface, testing etc. complete.</p>	3				3	no.