

जा.क्र.शावैमहाआ/बांधकाम/645/२६

दि. १३.०२.२०२६

मुख्य प्रशासकीय इमारती समोर अधिकारी व कर्मचाऱ्यांकरिता वाहन पार्किंग शेड तयार करणे जाहिर ई-दरपत्रक सूचना

शासकीय वैद्यकीय महाविद्यालय, अमरावती च्या मुख्य प्रशासकीय इमारती समोर अधिकारी व कर्मचाऱ्यांकरिता वाहन पार्किंग शेड तयार करणे करिता इच्छुक पुरवठादारांकडून द्विलिफाफा पध्दतीन दरपत्रक मागविण्यात येत आहे. सदर कालावधी दरनिश्चिती पत्र निघाल्याच्या दिवसापासून १८० दिवसांकरिता राहील.

- १) **तांत्रिक लिफाफा** –या लिफाफ्यामध्ये पुरवठादाराने बांधकामा बाबतचा परवाना, भूतकाळातील कामाचा अनुभव प्रमाणपत्र, साईड इंजिनियर नियुक्ती बाबतचे प्रमाणपत्र, कामगाराची नोंदणी विमा आणि सुरक्षीततेबाबतचे कागदपत्र जीएसटी प्रमाणपत्र व पॅन कार्ड, आधारकार्ड या कागदपत्राच्या छ्यांकित प्रती टाकुन तो मोहोरबंद करण्यात यावा त्यावर स्पष्ट शब्दात तांत्रिक बाबीचा लिफाफा असे नमुद करून स्वतःचे नाव व पत्ता व लिहावा त तो मोहोरबंद करावा.
- २) **किमंतीचा लिफाफा** - ज्यामध्ये दर नमुद असलेला कागद स्वाक्षरी व सहीनिशी टाकण्यात यावा व त्यावर स्पष्ट अक्षरात किमंतीचा लिफाफा नमुद करून स्वतःचे नाव व पत्ता लिहावा व तो देखील मोहोर बंद करण्यात यावा.

उपरोक्त दोन्ही लिफाफे एका मोठ्या लिफाफ्यामध्ये टाकूण दरपत्रक अधिष्ठाता, शासकीय वैद्यकीय महाविद्यालय, अमरावती यांचे नावे सादर करावयाचे असून दरपत्रकाच्या लिफाफ्यावर शासकीय वैद्यकीय महाविद्यालयाकरिता आवश्यक असलेल्या मुख्य प्रशासकीय इमारती समोर अधिकारी व कर्मचाऱ्यांकरिता वाहन पार्किंग शेड तयार करणे करिता दरपत्रक असे स्पष्ट नमुद करण्यात यावे. स्वतःचे नाव व पत्ता लिहावा अशा प्रकारे तयार करण्यत आलेले दरपत्रक दि. २५/०२/२०२६ रोजी सायंकाळी ०६:०० वाजेपर्यंत कार्यालयात आणून देण्यात यावे. तांत्रिक लिफाफा मध्ये दराचा उल्लेख करू नये. त्यामध्ये दर आढळल्यास दरपत्रक अग्राह समजन्यात येईल.

प्राप्त होणाऱ्या दरपत्रकातील तांत्रिक लिफाफे दि. २६/०२/२०२६ रोजी दु. १२:०० वाजता अधिष्ठाता, शासकीय वैद्यकीय महाविद्यालय, अमरावती यांच्या दालणामध्ये उघडण्यात येईल. सर्व प्रथम तांत्रिक बाबीचे लिफाफे उघडण्यात येईल. तांत्रिक बाबीची पुरता झाली नसल्यास संबंधीत पुरवठादाराचे दरपत्रक रद्द समजण्यात येईल व त्याचे किमंतीचे लिफाफे उघडण्यात येणार नाही. इच्छुक पुरवठादारास सदर सभेस उपस्थित राहता येईल.

जिथे दर द्यावयाचे नाही तिथे इच्छुक नाही असे स्पष्ट नमुद करावे. ती जागा रिकामी सोडण्यात येवू नये. सर्व दर हे एका नगाकरिता सर्व कर समाविष्ट करून नमुद करावे. अपूर्ण माहितीसह प्राप्त होणारी दरपत्रक नाकारण्याचा अधिकारी अधिष्ठाता यांनी राखुन ठेवलेला आहे. तसेच यादी मधील काही बाबी किंवा मागविण्यात येणाऱ्या संपूर्ण दरपत्रकाची प्रक्रिया रद्द करण्याचा अधिकारी अधिष्ठाता यांनी राखुन ठेवलेला आहे.

दर हे पेनने लिहान्यात येऊ नये ते प्रिंट केलेले असावे. हसताक्षरात लिहिलेले दरपत्रक रद्द करण्यात येईल. दरनिश्चिती झालयावर आवश्यकतेनुसार वेळोवेळी आदेश काढण्यात येईल. आदेश प्राप्त होताच १० दिवसांत आदेशातील मालाचा पुरवठा करणे बंधनकारक राहील.

न्युनतम ठरणाऱ्या पुरवठादारास नमुद विनिदिष्टांप्रमाणे सदर साहित्याचे पुरवठा करणे बंधनकारक राहील. अन्यथा पुरवठा करण्यात आलेले साहित्य तातडीने बदलून देण्याचे करावे. तसेच सदर साहित्याचा पुरवठा करणे बंधनकारक राहील. त्याकरिता कोणत्याही प्रकारचा अगाऊचा खर्च या संस्थेमार्फत अदा करण्यात येणार नाही.

सदर दरपत्रकासंबंधी आपणास काही तक्रार या कार्यालयास दाखल करावयाची असल्यास प्रथम आपण या कार्यालयात तक्रार संबंधी रु. १०,०००/- शासन खाती जमा करावे लागेल. जर आपण दाखल केलैल्या तक्रारीत या कार्यालयास काही तथ्य आढळून आल्यास आपणास आपण शासन खाती जमा केलेली रु. १०,०००/- रक्कम परत करण्यात येईल. तक्रारीमध्ये काही तथ्य न आढळल्यास रु. १०,०००/- रक्कम परत करता येणार नाही व ती रक्कम शासन खाती जमा करण्यात येईल.

Ch. Rat 13-02-2026

(डॉ. एन. जी. राऊत)

अधिष्ठाता

शासकीय वैद्यकीय महाविद्यालय, अमरावती

Government Medical College, Amravati

E Quotation for Construction of Vehicles Parking Shed at GMC, Amravati Tq. Dist. Amravati

| Item No. | Item of Work | Rate with GST |
|-----------------|--|----------------------|
| 1 | Excavation for foundation in earth, soil of all types, sand, gravel and soft murum, including removing the excavated material up to a distance of 50 m. beyond the building area and stacking and spreading as directed, dewatering, preparing the bed for the foundation and necessary back filling, ramming, watering including shoring and strutting etc. complete. (Lift upto 1.5 m.) By Mechanical Means | |
| 2 | Excavation for foundation in hard murum including removing the excavated material upto distance of 50 metres beyond the building area and stacking and spreading as directed, dewatering, preparing the bed for the foundation and necessary back filling, ramming, watering including shoring and strutting etc. complete. (Lift upto 1.50 m) By | |
| 3 | Providing soling using 80 mm size trap metal in 15 cm. layer including filling voids with Crushed sand/grit, ramming, watering etc. complete. | |
| 4 | Providing and laying Cast in situ/Ready Mix cement concrete in M-10 of trap/ granite/ quartzite/ gneiss metal for foundation and bedding including bailing out water, Steel centering, formwork, laying/pumping, compacting, roughening them if special finish is to be provided, finishing if required and curing complete, with fully automatic micro processor based PLC with SCADA enabled reversible Drum Type mixer/concrete Batch mix plant (Pan mixer) etc. complete. With fine aggregate (Crushed sand VSI Grade) | |
| 5 | Providing and laying Cast in situ/Ready Mix cement concrete in M-10 of trap/ granite/ quartzite/ gneiss metal for foundation and bedding including bailing out water, Steel centering, formwork, laying/pumping, compacting, roughening them if special finish is to be provided, finishing if required and curing complete, with fully automatic micro processor based PLC with SCADA enabled reversible Drum Type mixer/concrete Batch mix plant (Pan mixer) etc. complete. With fine aggregate (Crushed sand VSI Grade) | |
| 6 | Providing and laying in situ /Ready Mix cement concrete M-20 of trap/granite/quartzite/ gneiss metal for R.C.C. work in foundations like raft, strip foundations, grillage and footings of R.C.C. columns and steel stanchions etc. including bailing | |
| 7 | Providing and fixing heavy duty inter locking concrete RUBBER MOULD GLOSSY PAVING BLOCKS of 60 millimeter thickness of having a strength of 400 Kg/sq.m | |


 13-02-2026
Dean
Govt. Medical College
Amravati

| | | |
|----|--|--|
| 8 | <p>Providing and laying Cast in situ/Ready Mix cement concrete M-20 of trap / granite</p> <p>/quartzite/ gneiss metal for R.C.C. beams and lintels as per detailed designs and drawings or as directed including steel centering, formwork, cover blocks, laying/pumping, compaction and roughening the surface if special finish is to be provided and curing etc. complete. (Excluding reinforcement and structural steel). with fully automatic micro processor based PLC with SCADA enabled reversible Drum Type mixer/ concrete Batch mix plant (Pan mixer) etc. complete. With fine aggregate (Crushed sand VSI Grade)</p> | |
| 9 | Providing and fixing in position TMT - FE - 500 bar reinforcement of various diameters for R.C.C. pile caps, footings, foundations, slabs, beams columns, canopies, staircase, newels, chajjas, lintels pardis, copings, fins, arches etc. as per detailed designs, drawings and schedules. including cutting, bending, hooking the bars, binding with wires or tack welding and supporting as required | |
| 10 | Providing second class Burnt Brick masonry with conventional/ I.S. type bricks in cement mortar 1:6 in foundations and plinth of inner walls/ in plinth external walls including bailing out water manually, striking joints on unexposed faces, raking out joints on exposed faces and watering etc. Complete. | |
| 11 | Providing and laying Cast in situ/Ready Mix cement concrete M-15 of trap/ granite/quartzite/gneiss metal for coping to plinth or parapet, moulded or chamfered as per drawing or as directed including steel centering, plywood/ steel formwork compacting, roughening them if special finish is to be provided, finishing uneven and honeycombed surface and curing etc. complete. The Cement Mortar 1:3 plaster is considered for rendering uneven and honeycombed surface only. Newly laid concrete shall be covered by gunny bag, plastic, tarpaulin etc. (Wooden centering will not be allowed.) With fine aggregate (Crushed sand VSI Grade) | |
| 12 | Filling in plinth and floors with contractors material/brought from outside and approved by Engineer incharge in layers of 15 cm to 20 cm including watering and compaction etc. complete | |
| 13 | Providing internal cement plaster 20mm thick in Single coats in cement mortar 1:4 without neeru finish, to concrete, brick surface, in all positions including scaffolding and curing etc. complete | |
| 14 | Providing and applying Two coats of wall care Putty on plastered surface and Ceiling and Walls to prepare surface even and smooth of approved make, etc complete. | |
| 15 | Providing and laying cement concrete flooring 40 mm thick with M15 cement concrete laid to proper level and slope in alternate bays including compaction, filling joints, marking lines to give the appearance of tiles of 30 cm x 30 cm or other size laid diagonally /square etc finishing smooth (with extra cement) in any colour as directed and curing etc. complete. with Crushed sand VSI Grade | |

| | | |
|----|---|--|
| 16 | Providing and fabricating structural steel work in rolled sections like joists, channels, angles, tees etc. as per detailed design and drawings or as directed including cutting, fabricating, hoisting, erecting, fixing in position making riveted / bolted /welded connections without connecting plates, braces etc. and including one coat of anticorrosive paint and over it two coats of oil painting of approved quality and shade etc complete | |
| 17 | providing and fixing colour coated Zincalume (R) AZ150 (min 150 gms/sq.mt. total on each side) profiled sheets for roofing. The feed material is manufactured out of nominal 0.45 mm Base Metal Thickness (BMT) (0.5 mm TCT), Hi-strength steel with min.550 MPa yield strength, metallic hot dip coated with Aluminium-Zinc alloy (55% aluminium 43.4% zinc 1.6% silicon) with COLORBOND (R) steel quality super durable polyester paint coat (with inorganic pigment). The paint shall have a total coating thickness of nominal 35 um, comprising of nominal 25 um exterior coat on top surface and nominal 10 um reverse coat on back surface. Profile sheet shall have nom. 950- 1050 mm effective cover width and nominal 25-30 mm deep ribs | |
| 18 | Providing and fixing plain zinc sheeting of 0.80 mm thick (22 B.W.G.) over the ridge hip or valley to galvanized iron sheet roofing including all fastening and bolt galvanised iron screws and bolts, lead and bitumen washers etc. complete.(Weight of 6.8) | |
| 19 | Royalty charges Sand | |
| 20 | Royalty Charges Murum/80mm | |
| 21 | Basic test of cement | |
| 22 | Basic test of Aggregate Water Absorption, Sp Gravity, Impact/ crushing value | |
| 23 | test of Sieve analysis of aggregate | |
| 24 | test of Fineness modulus of sand | |
| 25 | test of Steel, Ultimate tensile strength, %elongation, Wt/meter | |
| 26 | test of Compression test of CC cube | |
| 27 | test of Bricks, Water absorption, Comp. strength, efflorescence | |
| | Total Amount | |

The Detail MEASUREMENT of the said work is attached Herewith Below.

Raut 13.02.2026

(Dr.N.G.Raut)

Dean

Government Medical College, Amravati

Dean
Govt. Medical College
Amravati

NAME OF WORK :

Construction of Vehicles Parking Shed at GMC, Amravati. Tq. Dist. Amravati.

MEASUREMENT

| Item No. | Item of Work | No | L | B | H | Quantity | Unit |
|----------|--------------|----|---|---|---|----------|------|
|----------|--------------|----|---|---|---|----------|------|

1 Excavation for foundation in earth, soil of all types, sand, gravel and soft murum, including removing the excavated material up to a distance of 50 m. beyond the building area and stacking and spreading as directed, dewatering, preparing the bed for the foundation and necessary back filling, ramming, watering including shoring and strutting etc. complete. (Lift upto 1.5 m.)
By Mechanical Means

| | | | | | | | |
|-------------|----|--------|----------|------|-------|--------|-----|
| for columns | 14 | x 1.20 | x 1.50 = | 1.22 | 30.74 | 30.744 | Cum |
|-------------|----|--------|----------|------|-------|--------|-----|

2 Excavation for foundation in hard murum including removing the excavated material upto distance of 50 metres beyond the building area and stacking and spreading as directed, dewatering, preparing the bed for the foundation and necessary back filling, ramming, watering including shoring and strutting etc. complete. (Lift upto 1.50 m) By Mechanical Means

| | | | | | | | |
|-------------|---|--------|----------|------|------|-------|-----|
| for columns | 0 | x 0.00 | x 0.00 = | 0.00 | 0.00 | 0.000 | Cum |
| for steps | 0 | x 0.00 | x 0.00 = | 0.00 | 0.00 | 0.000 | Cum |

3 Providing soling using 80 mm size trap metal in 15 cm. layer including filling voids with Crushed sand/grit, ramming, watering etc. complete.

| | | | | | | | |
|-------------|----|-----|-----|----------|------|-------|-----|
| for columns | 14 | 1.2 | 1.5 | x 0.15 = | 3.78 | 3.780 | Cum |
|-------------|----|-----|-----|----------|------|-------|-----|

| Item No. | Item of Work | No | L | B | H | Quantity | Unit |
|----------|--|----|---------|----------|----------|----------|------|
| 4 | Providing and laying Cast in situ/Ready Mix cement concrete in M-10 of trap/ granite/ quartzite/ gneiss metal for foundation and bedding including bailing out water, Steel centering, formwork, laying/pumping, compacting, roughening them if special finish is to be provided, finishing if required and curing complete, with fully automatic micro processor based PLC with SCADA enabled reversible Drum Type mixer/concrete Batch mix plant (Pan mixer) etc. complete. With fine aggregate (Crushed sand VSI Grade) | | | | | | |
| | for columns | 14 | x 1.20 | x 1.50 | x 0.10 = | 2.52 | |
| | | | | | | 2.520 | Cum |
| 5 | Providing and laying in situ /Ready Mix cement concrete M-20 of trap / granite /quartzite/ gneiss metal for R.C.C. work in foundations like raft, strip foundations, grillage and footings of R.C.C. columns and steel stanchions etc. including bailing out water, Steel centering formwork, | | | | | | |
| | for pedestals | 14 | x 1.00 | x 1.00 | x 0.91 = | 12.74 | |
| | | | | | | 12.740 | Cum |
| 16 | Providing and fabricating structural steel work in rolled sections like joists, channels, angles, tees etc. as per detailed design and drawings or as directed including cutting, fabricating, hoisting, erecting, fixing in position making riveted / bolted /welded connections without connecting plates, braces etc. and including one coat of anticorrosive paint and over it two coats of oil painting of approved quality and shade | | | | | | |
| | square section of 49.5x2.9 mm vertical post | 14 | x 3.06 | x 5.95 = | kg/mtr | 0.254 | |
| | square pipe vertical comp.member 49.5x2.9 | 8 | x 1.22 | x 5.95 = | kg/mtr | 0.058 | |
| | for rafters 49.5x2.9 mm (two side rafters) | 14 | x 7.92 | x 4.90 = | kg/mtr | 0.543 | |
| | Square section of 38x2 mm purlins | 5 | x 43.72 | x 2.75 = | kg/mtr | 0.601 | |
| | square pipes for bracing 38x2 | 14 | x 1.20 | x 2.75 = | kg/mtr | 0.046 | |
| | horizontal bracing 38x2 | 8 | x 1.52 | x 2.75 = | kg/mtr | 0.033 | |
| | Add 10% for plates and cleats | | | | kg/mtr | 0.1535 | |
| | | | | | | 1.6885 | MT |

